

Nominal	Phase Conductor				Lighting Conductor		Neutral Conductor		
	Cross-Section Area	Stranding N°	Insulated (mm)	Max. D.C. Resistance (ohm/km 20 °C)	Current Carrying air 30°C Capacity (A)	Insulated (mm)	Max. D.C. Resistance (ohm/km 20 °C)	Insulated (mm)	Max. D.C. Resistance (ohm/km 20 °C)
1X16+NA25mm2	7	1.14	1.91	85			1.14	1.3305	7.74
1X25+NA25mm2	7	1.14	1.20	114			1.14	1.3305	7.74
1X35+NA25mm2	7	1.14	0.868	141			1.14	1.3305	7.74
2X16+NA25mm2	7	1.14	1.91	89			1.14	1.3305	7.74
2X25+NA25mm2	7	1.14	1.20	114			1.14	1.3305	7.74
2X35+NA25mm2	7	1.14	0.868	141			1.14	1.3305	7.74
2X50+NA35mm2	7	1.52	0.641	171			1.14	0.9651	10.81
2X70+NA50mm2	19	1.52	0.443	215			1.52	0.6755	15.44
2X95+NA70mm2	19	1.52	0.32	262			1.52	0.4825	20.95
2X120+NA70mm2	19	2.04	0.253	303			1.52	0.4825	20.95
3X16+NA25mm2	7	1.14	1.91	85			1.14	1.3305	7.74
3X25+NA25mm2	7	1.14	1.20	114			1.14	1.3305	7.74
3X35+NA25mm2	7	1.14	0.868	141			1.14	1.3305	7.74
3X50+NA35mm2	7	1.52	0.641	171			1.14	0.9651	10.81
3X70+NA50mm2	19	1.52	0.443	215			1.52	0.6755	15.44
3X95+NA70mm2	19	1.52	0.32	262			1.52	0.4825	20.95
3X120+NA70mm2	19	2.04	0.253	303			1.52	0.4825	20.95
2X16+1X16+NA25mm2	7	1.14	1.91	85	1.14	1.91	1.14	1.3305	7.74
2X25+1X16+NA25mm2	7	1.14	1.20	114	1.14	1.91	1.14	1.3305	7.74
2X35+1X16+NA25mm2	7	1.14	0.868	141	1.14	1.91	1.14	1.3305	7.74
2X50+1X16+NA35mm2	7	1.52	0.641	171	1.14	1.91	1.14	0.9651	10.81
2X70+1X16+NA50mm2	19	1.52	0.443	215	1.14	1.91	1.52	0.6755	15.44
2X95+1X16+NA70mm2	19	1.52	0.32	262	1.14	1.91	1.52	0.4825	20.95
2X120+1X16+NA70mm2	19	2.04	0.253	303	1.14	1.91	1.52	0.4825	20.95
3X16+1X16+NA25mm2	7	1.14	1.91	85	1.14	1.91	1.14	1.3305	7.74
3X25+1X16+NA25mm2	7	1.14	1.20	117	1.14	1.91	1.14	1.3305	7.74
3X35+1X16+NA25mm2	7	1.14	0.868	114	1.14	1.91	1.14	1.3305	7.74
3X50+1X16+NA35mm2	19	1.52	0.641	171	1.14	1.91	1.14	0.9651	10.64
3X70+1X16+NA50mm2	19	1.52	0.443	215	1.14	1.91	1.52	0.6755	15.44
3X70+1X25+NA50mm2	19	1.52	0.443	215	1.14	1.20	1.52	0.6755	15.44
3X95+1X16+NA70mm2	19	1.52	0.32	262	1.14	1.91	1.52	0.4825	20.95
3X120+1X16+NA70mm2	19	2.04	0.253	303	1.14	1.91	1.52	0.4825	20.95