

Nominal	Phase Conductor			Lighting Conductor			Neutral Conductor		
	Cross-Section Area	Stranding and wires (mm)	Max. D.C. Resistance (ohm/km 20 °C)	Current Carrying air 30 °C Capacity (A)	Stranding and wires (mm)	Max. D.C. Resistance (ohm/km 20 °C)	Current Carrying air 30 °C Capacity (A)	Overall Dia. (mm)	Stranding and wires (mm)
2X16mm ²	1.14	1.91	89				3.2	0.80	8.14
2X25mm ²	1.14	1.20	114				3.2	0.80	8.14
2X35mm ²	1.14	0.868	141				3.2	0.80	8.14
3X16mm ²	1.14	1.91	89				3.2	0.80	8.14
3X25mm ²	1.14	1.20	114				3.2	0.80	8.14
3X35mm ²	1.14	0.868	141				3.2	0.80	8.14
3X50mm ²	1.52	0.641	171				3.2	0.80	8.14
2X16+1X16mm ²	1.14	1.91	89	1.14	1.91	89	3.2	0.80	8.14
2X25+1X16mm ²	1.14	1.20	114	1.14	1.91	89	3.2	0.80	8.14
2X35+1X16mm ²	1.14	0.868	141	1.14	1.91	89	3.2	0.80	8.14
2X50+1X16mm ²	1.52	0.641	171	1.14	1.91	89	3.2	0.80	8.14
2X70+1X16mm ²	1.52	0.443	215	1.14	1.91	89	3.2	0.80	8.14
3X16+2X16mm ²	1.14	1.91	89	1.14	1.91	89	3.2	0.80	8.14
3X25+2X16mm ²	1.14	1.20	114	1.14	1.91	89	3.2	0.80	8.14
3X35+2X16mm ²	1.14	0.868	141	1.14	1.91	89	3.2	0.80	8.14
3X50+2X16mm ²	1.52	0.641	171	1.14	1.91	89	3.2	0.80	8.14
3X50+2X25mm ²	1.52	0.641	171	1.14	1.20	117	3.2	0.80	8.14
3X70+2X16mm ²	1.52	0.443	215	1.14	1.91	89	3.2	0.80	8.14
3X70+2X35mm ²	1.52	0.443	215	1.14	0.868	141	3.2	0.80	8.14